

# 530 Post & Pole Peeler

## Standard Equipment

- Center section complete with debarking mechanism, combination carbide teeth and planer knife cutterhead with hydraulic table lock assembly
- 6mt infeed conveyor section with kicker assembly and hydraulic drive
- 6mt outfeed conveyor section, hourglass roll design, with 2-way kicker assembly and hydraulic drive
- Hydraulic controlled infeed shoe and top yoke assembly
- Support legs 990mm from bottom of leg to top of infeed conveyor section
- Motor base (specify frame size) and V-belt drive

## Specifications

### General

Power \_\_\_\_\_ Electric, diesel or PTO  
 Horsepower \_\_\_\_\_ 50 HP  
 Production \_\_\_\_\_ Up to 12 m/mm  
 Capacity \_\_\_\_\_ 50mm – 300mm diameter, 1.8mt-7.6mt long  
 Weight \_\_\_\_\_ 5000kg  
 Length \_\_\_\_\_ 7.6mt infeed/outfeed accommodates 9mt material  
 Width \_\_\_\_\_ 3mt  
 Height \_\_\_\_\_ 2.5mt w/blower, 2.2mt w/o blower  
 Discharge \_\_\_\_\_ Bark auger & blower, barn sweep  
 Debarker type \_\_\_\_\_ Split cutterhead debarks, then planes

### Options

- Machine to accommodate 9.0mt poles (7.6mt infeed, 7.6mt outfeed)
- Bark blower and feed auger for waste removal complete with drive, elbow blowpipe, and connection collar
- Blowpipe 20cm x 25cm extension section with connecting collar 530 center section
- Infeeds and outfeeds sold separately (complete with drive)
- Elevated operator's console, complete with access ladder, seat, + hose hookup.
- All weather cab (operator's console must be added when ordering cab)
- Side mounted combination air conditioner/heater unit for cab enclosure.

