

Chip-Pacs

Features

- Screen mounts above chipper for no wasted space
- 1.5m x 1.5m screen is utilized on 48" Chip-Pac; 1.8m x 1.8m screen utilised on 58" Chip-Pac
- Acceptable chips are able to be discharged on either side of the Chip-pac
- Flexible rods support the screen-no knuckle joints are used

Optional Equipment

58" Chip-Pac

- 3-HP fines blower with 3-HP electric motor mounted on swivel base
- Hydraulic 10-HP, 30HP, 40HP chip blower mounted on swivel base with single "S" pipe
- Valve for dual loading
- Convert horizontal feed to drop feed chipper
- Convert 3-knife to 4-knife or 6-knife chipper

48" Chip-Pac

- 3-HP fines blower with 3-HP electric motor mounted on swivel base
- 10-HP electric chip blower with 10-HP electric motor mounted on swivel base with single "S" pipe
- 30-HP electric super blower with 30-HP electric motor mounted on swivel base with single "S" pipe

Specifications

48" Chip-Pac

Power _____ 75 – 150 HP Electric or diesel
 Capacity _____ 28cm diameter
 Options _____ 3, 4 or 6 knives
 Weight _____ 5080kg
 Width _____ 193cm x 178cm
 Height _____ 234cm
 Space Required _____ 58cm to 279cm
 Screen size _____ 1.5m x 1.5m
 Foundation _____ Cement slab

58" Chip-Pac

Power _____ 75- 250 HP Electric or diesel
 Capacity _____ 38cm diameter
 Options _____ 3, 4 or 6 knives
 Weight _____ 7094kg
 Width _____ 223cm
 Depth _____ 220.9cm
 Height _____ 370.8cm w/cyclone
 Space Required _____ 393.7cm to 279cm
 Screen size _____ 1.8m x 1.8m
 Foundation _____ Cement slab

Standard Equipment

48" & 58" Chip-Pac

- Blowpipe and cyclone
- Overs return to chipper spout
- Double pump hydraulic system includes oil tank, valve bank, chipper sheave, and bushing, less base (D Model)
- Motor base including belt shield and take-up rails (E Model)
- Morbark Australia Model 48", 3-knife, horizontal feed, end discharge chipper (specify desired chip size setting)
- 1.5m x 1.5m Chip Screen with 2-HP electric drive

