

Stationary Chippers

Options

- (6) steel chipper support legs to accommodate 1.5mt elevation to bottom of infeed spout
- Transition piece for 48", 58", and 66" chippers to go from square discharge to round blowpipe.
- 250mm - 300mm round blowpipe straight pipe
- Hydraulic telescoping swivel discharge spout. (requires auxiliary hydraulic power supply to operate)
- Hydraulic hood opener includes cylinder and lugs. Does not include hydraulic power supply to valve to operate same. (Available for 75", 83", and 96" chippers)
- Manual swivel discharge spout. (includes transition piece)
- 300mm Black Blowpipe with 10mm wall thickness bent 90 degrees. Height is 1.2mt and length is 2.3mt
- Feed wheel assembly for 75" & 83" chippers includes hydraulic drive, forward and reverse controls for drive wheels and controls to raise and lower feed wheel assembly. (requires hydraulic power supply from another source)
- 100mm Thick chipper fronts Heavy duty fan blades with T-1 inserts
- 130mm thick chipper disc



Specifications

96" Chipper

Capacity _____ 760mm round wood
 Length _____ 2.65mt
 Weight _____ 14,000kg
 Width _____ 1.9mt
 Height _____ 2.65mt

83" Chipper

Capacity _____ 685mm round wood
 Length _____ 2.35mt
 Weight _____ 8700kg
 Width _____ 1.6mt
 Height _____ 2.3mt

75" Chipper

Capacity _____ 560mm round wood
 Length _____ 2.10mt
 Weight _____ 7100kg
 Width _____ 2.05mt
 Height _____ 2.15mt

66" Chipper

Capacity _____ 460mm round wood
 Length _____ 2.10mt
 Weight _____ 5000kg
 Width _____ 1.75mt
 Height _____ 1.9mt

58" Chipper

Capacity _____ 380mm round wood
 Length _____ 1.70mt
 Weight _____ 3800kg
 Width _____ 1.50mt
 Height _____ 1.65mt

48" Chipper

Capacity _____ 380mm round wood
 Length _____ 1.7mt
 Weight _____ 3800kg
 Width _____ 1.7mt
 Height _____ 1.65mt